



ORLAND PARK

DEVELOPMENT SERVICES DEPARTMENT
14700 RAVINIA AVENUE
ORLAND PARK, ILLINOIS 60462
708-403-5300
www.orlandpark.org

PERMIT # _____

Permeable Paver Installation Requirements

A series of interlocking concrete pavers that contain drainage voids for passing runoff to the sub-surface, where the water is further conveyed through base materials into the ground or storm drain system.

Requirements:

- Supply a cut sheet showing materials and details of aggregate, bedding, base and sub-base
- Must use a permeable paver
- Install underdrains as required
- Optional geotextile under subgrade

AGGREGATE Material being used _____

- ASTM No 9 (1/4" stone) or ASTM No 8

BEDDING Material being used _____ Depth _____

- ASTM No 8 (3/8" stone) – at least 1-1/2 to 2" thick

BASE Material being used _____ Depth _____

- ASTM No 57 (3/4" open graded stone) or
- ASTM No 467 (1-1/2" open graded stone) – 4-6" thick

SUB-BASE Material being used _____ Depth _____

- ASTM No 2 (2-1/2" open graded stone) – 6-12" thick

TWO Inspections required: Base inspection required showing progressive sub-base, base and bedding. Final inspection required after joint aggregate installed. Inspections may be submitted: In person at Development Services Department,
on website at www.orlandpark.org, or email to inspectionrequest@orlandpark.org.
Inspection requests are NOT taken over the phone.

PRINT NAME _____ SIGNATURE _____ DATE _____